

RAINTAG ACTIVE TAG LONG RANGE READER



► MODEL FEATURES

- Up To 5 Meters Reading Range
- Adjustable Reading Range
- High Immunity To Noise
- Integrated Antenna
- Wireless Communication Design for Retrofitting
- Long Battery Life (replaceable)
- Low Operating Frequency. Better Penetration Through Vehicle Tinting



LATTICE RRAINTAG



RAINTAG

ACTIVE TAG LONG RANGE READER

TECHNICAL SPECIFICATION

➤ RS-5M-W (STANDARD READER)

DESCRIPTION	RS-5M-W (STANDARD READER only)
Operating Frequency	125kHz
Interface	Wiegand 26/37/44bits, RS232
Power	11-14VDC
Indicator	Red, Green, Yellow, Beeper
Reading Distance	2-5 meters adjustable
Response Time	200ms
Environment Rating	IP 65
Dimensions/Weight	250x160x58mm/0.5Kg

➤ RS-5M-CW (READER WITH BUILT-IN CONTROLLER)

DESCRIPTION	RS-5M-CW (BUILT-IN CONTROLLER)
Card Holder Capacity	10,000
Transactions	30,000
Communication	IEEE802.15.4/Wireless 2.45Ghz/TCP/IP/RS232/485
Anti-Passback	YES with Multiple IN/OUTs
Management Software	Integrated with Lattice ACS

➤ RAIN TAG

DESCRIPTION	RAINTAG
Battery Life	Approximately 5 years depending on usage
Replaceable Battery	YES
Dimensions/Weight	55x86x6mm/15grams
Low Battery Warning	On Software and Reader Indications
Vehicle Tint	High Immunity to Vehicle Tinting